



Notice: Revised Pedernales Electric Cooperative Specifications

Posted June 9, 2025

Underground Installation Specifications

- Specification 520-010: *Pad for Service Meter Pedestal*
 - Revised reference to notes and details on 510-009.
 - Minor, non-technical drawing rearrangements.
- Specification 560-050: *Single-Phase Secondary Riser with Standoffs*
 - Revised title from *Single-Phase Riser with Standoffs* to *Single-Phase Secondary Riser with Standoffs*.
 - Revised minimum meter centerline height from 5' to 4' to align with meter loop specifications.
- Specification 560-051: *Single-Phase Secondary Riser with Standoffs to a Meter Rack*
 - Revised title from *Single-Phase Riser with Standoffs to a Meter Rack* to *Single-Phase Secondary Riser with Standoffs to a Meter Rack*.
 - Revised minimum meter centerline height from 5' to 3' and maximum meter centerline height from 6' to 5' to align with meter loop specifications.
- Specification 560-052: *Single-Phase Secondary Riser with Standoffs from Overhead Transformer*
 - Revised title from *600-Volt Underground Service from Overhead Transformer* to *Single-Phase Secondary Riser with Standoffs from Overhead Transformer*.
 - Revised minimum meter centerline height from 5' to 4' to align with meter loop specifications.

Note: *Summaries listed here and in previous notices primarily include revisions considered technically significant to the referenced specifications. Edits considered technically insignificant may not be listed.*